

Exclusive D (3 Pumps)		VOLTAGE	MAX POWER		CURR
	CODE	V-	kW	Hp	Range (A)
Exclusive D 3 / Mono	1071	1 - 230	2.2	3	0-18
Exclusive D 3 - 4/ Tri	15001	3 - 400	4	5.5	0-8.6
Exclusive D 3 - 5.5 / Tri	15002	3 - 400	5.5	7.5	0-11.6
Exclusive D 3 - 7.5 / Tri	15003	3 - 400	7.5	10	0-15.8
Exclusive D 3 - 11 / Tri	15004	3 - 400	11	15	0-25
Exclusive D 3 - 15 / Tri	15005	3 - 400	15	20	0-32

Exclusive D (4 Pumps)		VOLTAGE	MAX POWER		CURR
	CODE	V-	kW	Hp	Range (A)
Exclusive D 4 / Mono	1081	1 - 230	2.2	3	0-18
Exclusive D 4 - 4/ Tri	15201	3 - 400	4	5.5	0-8.6
Exclusive D 4 - 5.5 / Tri	15202	3 - 400	5.5	7.5	0-11.6
Exclusive D 4 - 7.5 / Tri	15203	3 - 400	7.5	10	0-15.8
Exclusive D 4 - 11 / Tri	15204	3 - 400	11	15	0-25
Exclusive D 4 - 15 / Tri	15205	3 - 400	15	20	0-32

Exclusive S 1		VOLTAGE	MAX POWER		CURR
	CODE	V-	kW	Hp	Range (A)
Exclusive S 1 - 7.5 / Tri	16001	3 - 400	7.5	10	0-15.8
Exclusive S 1 - 11 / Tri	16002	3 - 400	11	15	0-25
Exclusive S 1 - 15 / Tri	16003	3 - 400	15	20	0-31.9
Exclusive S 1 - 18.5 / Tri	16004	3 - 400	18.5	25	0-37.1
Exclusive S 1 - 22 / Tri	16005	3 - 400	22	30	0-42.7
Exclusive S 1 - 30 / Tri	16006	3 - 400	30	40	0-57.6
Exclusive S 1 - 37 / Tri	16007	3 - 400	37	50	0-70.2
Exclusive S 1 - 45 / Tri	16008	3 - 400	45	60	0-83.5
Exclusive S 1 - 55 / Tri	16009	3 - 400	55	75	0-100.9
Exclusive S 1 - 75 / Tri	16010	3 - 400	75	100	0-140.7
Exclusive S 1 - 90 / Tri	16011	3 - 400	90	125	0-165.1
Exclusive S 1 - 110 / Tri	16012	3 - 400	110	150	0-201.9
Exclusive S 1 - 132 / Tri	16013	3 - 400	132	180	0-242.2
Exclusive S 1 - 160 / Tri	16014	3 - 400	160	220	0-290.6
Exclusive S 1 - 185 / Tri	16015	3 - 400	185	250	0-332.4
Exclusive S 1 - 200 / Tri	16016	3 - 400	200	270	0-355.4
Exclusive S 1 - 250 / Tri	16017	3 - 400	250	340	0-444.3
Exclusive S 1 - 315 / Tri	16018	3 - 400	315	430	0-553.6
Exclusive S 1 - 355 / Tri	16019	3 - 400	355	485	0-623.9
Exclusive S 1 - 400 / Tri	16020	3 - 400	400	544	0-703

Exclusive S 2		VOLTAGE	MAX POWER		CURR
	CODE	V-	kW	Hp	Range (A)
Exclusive S 2 - 7.5 / Tri	16201	3 - 400	7.5	10	0-15.8
Exclusive S 2 - 11 / Tri	16202	3 - 400	11	15	0-25

Exclusive S 2 - 15 / Tri	16203	3 - 400	15	20	0-31.9
Exclusive S 2 - 18.5 / Tri	16204	3 - 400	18.5	25	0-37.1
Exclusive S 2 - 22 / Tri	16205	3 - 400	22	30	0-42.7
Exclusive S 2 - 30 / Tri	16206	3 - 400	30	40	0-57.6
Exclusive S 2 - 37 / Tri	16207	3 - 400	37	50	0-70.2
Exclusive S 2 - 45 / Tri	16208	3 - 400	45	60	0-83.5
Exclusive S 2 - 55 / Tri	16209	3 - 400	55	75	0-100.9
Exclusive S 2 - 75 / Tri	16210	3 - 400	75	100	0-140.7
Exclusive S 2 - 90 / Tri	16211	3 - 400	90	125	0-165.1
Exclusive S 2 - 110 / Tri	16212	3 - 400	110	150	0-201.9
Exclusive S 2 - 132 / Tri	16213	3 - 400	132	180	0-242.2
Exclusive S 2 - 160 / Tri	16214	3 - 400	160	220	0-290.6
Exclusive S 2 - 185 / Tri	16215	3 - 400	185	250	0-332.4
Exclusive S 2 - 200 / Tri	16216	3 - 400	200	270	0-355.4
Exclusive S 2 - 250 / Tri	16217	3 - 400	250	340	0-444.3
Exclusive S 2 - 315 / Tri	16218	3 - 400	315	430	0-553.6
Exclusive S 2 - 355 / Tri	16219	3 - 400	355	485	0-623.9
Exclusive S 2 - 400 / Tri	16220	3 - 400	400	544	0-703

Exclusive S 3		VOLTAGE	MAX POWER		CURR
	CODE	V-	kW	Hp	Range (A)
Exclusive S 3 - 7.5 / Tri	16301	3 - 400	7.5	10	0-15.8
Exclusive S 3 - 11 / Tri	16302	3 - 400	11	15	0-25
Exclusive S 3 - 15 / Tri	16303	3 - 400	15	20	0-31.9
Exclusive S 3 - 18.5 / Tri	16304	3 - 400	18.5	25	0-37.1
Exclusive S 3 - 22 / Tri	16305	3 - 400	22	30	0-42.7
Exclusive S 3 - 30 / Tri	16306	3 - 400	30	40	0-57.6
Exclusive S 3 - 37 / Tri	16307	3 - 400	37	50	0-70.2
Exclusive S 3 - 45 / Tri	16308	3 - 400	45	60	0-83.5
Exclusive S 3 - 55 / Tri	16309	3 - 400	55	75	0-100.9
Exclusive S 3 - 75 / Tri	16310	3 - 400	75	100	0-140.7
Exclusive S 3 - 90 / Tri	16311	3 - 400	90	125	0-165.1
Exclusive S 3 - 110 / Tri	16312	3 - 400	110	150	0-201.9
Exclusive S 3 - 132 / Tri	16313	3 - 400	132	180	0-242.2
Exclusive S 3 - 160 / Tri	16314	3 - 400	160	220	0-290.6
Exclusive S 3 - 185 / Tri	16315	3 - 400	185	250	0-332.4
Exclusive S 3 - 200 / Tri	16316	3 - 400	200	270	0-355.4
Exclusive S 3 - 250 / Tri	16317	3 - 400	250	340	0-444.3
Exclusive S 3 - 315 / Tri	16318	3 - 400	315	430	0-553.6
Exclusive S 3 - 355 / Tri	16319	3 - 400	355	485	0-623.9
Exclusive S 3 - 400 / Tri	16320	3 - 400	400	544	0-703

Exclusive S 4		VOLTAGE	MAX POWER		CURR
	CODE	V-	kW	Hp	Range (A)
Exclusive S 4 - 7.5 / Tri	16401	3 - 400	7.5	10	0-15.8
Exclusive S 4 - 11 / Tri	16402	3 - 400	11	15	0-25
Exclusive S 4 - 15 / Tri	16403	3 - 400	15	20	0-31.9

Exclusive S 4 - 18.5 / Tri	16404	3 - 400	18.5	25	0-37.1
Exclusive S 4 - 22 / Tri	16405	3 - 400	22	30	0-42.7
Exclusive S 4 - 30 / Tri	16406	3 - 400	30	40	0-57.6
Exclusive S 4 - 37 / Tri	16407	3 - 400	37	50	0-70.2
Exclusive S 4 - 45 / Tri	16408	3 - 400	45	60	0-83.5
Exclusive S 4 - 55 / Tri	16409	3 - 400	55	75	0-100.9
Exclusive S 4 - 75 / Tri	16410	3 - 400	75	100	0-140.7
Exclusive S 4 - 90 / Tri	16411	3 - 400	90	125	0-165.1
Exclusive S 4 - 110 / Tri	16412	3 - 400	110	150	0-201.9
Exclusive S 4 - 132 / Tri	16413	3 - 400	132	180	0-242.2
Exclusive S 4 - 160 / Tri	16414	3 - 400	160	220	0-290.6
Exclusive S 4 - 185 / Tri	16415	3 - 400	185	250	0-332.4
Exclusive S 4 - 200 / Tri	16416	3 - 400	200	270	0-355.4
Exclusive S 4 - 250 / Tri	16417	3 - 400	250	340	0-444.3
Exclusive S 4 - 315 / Tri	16418	3 - 400	315	430	0-553.6
Exclusive S 4 - 355 / Tri	16419	3 - 400	355	485	0-623.9
Exclusive S 4 - 400 / Tri	16420	3 - 400	400	544	0-703

ARENT	BOX DIMENSIONS			WEIGHT	
Max (A)	D	E	G	Material	KG
18	600	400	200	Metallic	
0-8.6	600	400	200	Metallic	
0-11.6	600	400	200	Metallic	
0-15.8	600	400	200	Metallic	
25	600	400	200	Metallic	
32	600	400	200	Metallic	

ARENT	BOX DIMENSIONS			WEIGHT	
Max (A)	D	E	G	Material	KG
18	600	400	200	Metallic	
0-8.6	600	400	200	Metallic	
0-11.6	600	400	200	Metallic	
0-15.8	600	400	200	Metallic	
25	600	400	200	Metallic	
32	600	400	200	Metallic	

ARENT	BOX DIMENSIONS			WEIGHT	
Max (A)	D	E	G	Material	KG
15.8	400	300	175	ABS	
25	400	300	175	ABS	
31.9	600	400	200	Metallic	
37.1	600	400	200	Metallic	
42.7	600	400	200	Metallic	
57.6	600	400	200	Metallic	
70.2	600	400	200	Metallic	
83.5	700	500	200	Metallic	
100.9	700	500	200	Metallic	
140.7	700	500	200	Metallic	
165.1	800	600	290	Metallic	
201.9	800	600	290	Metallic	
242.2	1000	700	320	Metallic	
290.6	1000	700	320	Metallic	
332.4	1200	800	340	Metallic	
355.4	1200	800	340	Metallic	
444.3	1200	800	340	Metallic	
553.6	1300	900	360	Metallic	
623.9	1300	900	360	Metallic	
703	1300	900	360	Metallic	

ARENT	BOX DIMENSIONS			WEIGHT	
Max (A)	D	E	G	Material	KG
15.8	600	400	200	Metallic	
25	600	400	200	Metallic	

31.9	600	400	200	Metallic	
37.1	600	400	200	Metallic	
42.7	700	500	260	Metallic	
57.6	700	500	260	Metallic	
70.2	800	600	290	Metallic	
83.5	1000	700	320	Metallic	
100.9	1000	700	320	Metallic	
140.7	1200	800	340	Metallic	
165.1	1400	800	340	Metallic	
201.9	1400	800	340	Metallic	
242.2	1800	950	360	Metallic	
290.6	1800	950	360	Metallic	
332.4	2000	1000	420	Metallic	
355.4	2000	1000	420	Metallic	
444.3	2000	1000	420	Metallic	
553.6	2100	1600	500	Metallic	
623.9	2100	1600	500	Metallic	
703	2100	1600	500	Metallic	

ARENT	BOX DIMENSIONS			WEIGHT	
Max (A)	D	E	G	Material	KG
15.8	600	500	260	Metallic	
25	600	500	260	Metallic	
31.9	600	600	290	Metallic	
37.1	600	700	320	Metallic	
42.7	700	700	320	Metallic	
57.6	700	800	340	Metallic	
70.2	800	800	340	Metallic	
83.5	1000	800	340	Metallic	
100.9	1000	950	360	Metallic	
140.7	1200	950	360	Metallic	
165.1	1400	1200	420	Metallic	
201.9	1400	1200	420	Metallic	
242.2	1800	1200	420	Metallic	
290.6	1800	1600	500	Metallic	
332.4	2000	1600	500	Metallic	
355.4	2000	1600	500	Metallic	
444.3	2000	1600	500	Metallic	
553.6	2100	1600	550	Metallic	
623.9	2100	1600	550	Metallic	
703	2100	1600	550	Metallic	

ARENT	BOX DIMENSIONS			WEIGHT	
Max (A)	D	E	G	Material	KG
15.8	800	600	290	Metallic	
25	800	600	290	Metallic	
31.9	800	600	290	Metallic	

37.1	1000	700	320	Metallic	
42.7	1000	700	320	Metallic	
57.6	1200	800	340	Metallic	
70.2	1400	800	340	Metallic	
83.5	1400	800	340	Metallic	
100.9	1800	950	360	Metallic	
140.7	1800	950	360	Metallic	
165.1	2000	1600	500	Metallic	
201.9	2000	1600	500	Metallic	
242.2	2000	1600	500	Metallic	
290.6	2200	1600	550	Metallic	
332.4	2200	1600	550	Metallic	
355.4	2200	1600	550	Metallic	
444.3	2200	1600	550	Metallic	
553.6	2400	1800	600	Metallic	
623.9	2400	1800	600	Metallic	
703	2400	1800	600	Metallic	